

中文的表格:

贴标速度	0.1-45米/分钟可调
贴标精度	±1mm (与被贴物的外形有关)
标签宽度	15-130 mm (标准宽度, 可以根据实际产品尺寸进行增加宽度)
标签最大长度	350 mm
盒子宽度	客户提供盒样 (空盒或装后贴标)
工作面高度	900mm (可以根据实际产品尺寸进行调整)
适用卷纸内径	152mm
标签卷最大外径	Φ500mm
贴标胶体	不干胶
使用电力	220V 50Hz 3000W
整机尺寸 (L×W×H)	3000* 1500* 1680mm
使用气压	3-5KG
整机重量	400 Kg

英文翻译:

Labeling Speed	0.1-45m/minute (adjustable)
Labeling Accuracy	±1mm (related to bottle's shape)
Label Width	Standard 15-130 mm(can increase according to bottle size)
Label Max. Length	350 mm
Bottle Diameter	Customer provide bottle samples(empty or filled)
Work-Surface Height	900mm (adjustable according to bottle size)
Inner Diameter of roll paper	152mm
Max. Outer Diameter of roll paper	Φ500mm
Labeling colloid	Adhesive
Electricity Power	220V 50Hz 3000W
Overall Dimensions (L×W×H)	3000* 1500* 1680mm
Operation Air Pressure	3-5KG
Operation Weight	400 Kg



Company Name: Feyvan Packing Machinery Co., Ltd.

Address:Jinggu Manufacture Park, No. 3 Lezhong Road, Suzhou City, Jiangsu Province

Contact Person:sales manager Peter

Phone/WhatsApp: 15862114537